

Full C-band 10W BUC

MODEL No. NJT5763 series

< Features >

- * **Wide band Radio Frequency**
 - Frequency: 5.85 to 6.725 GHz
(Standard C-band & Palala C-band)
- * **High Efficiency & Low Distortion**
 - P1dB: +40 dBm min. over temperature
 - IM3: -24 dBc @ Pout = +37 dBm
 - Power Consumption: 75 W
- * **Compact Size & Light Weight**
 - Weight: 3.2kg
- * **AC Power Option**
- * **LED Indicator**
- * **RoHS Compliance**



< Line-up >

Model No.	RF Frequency	Local Frequency	IF Frequency	Output Power @ P1dB	IF Connector	Power Supply	Port for Voltage Input	LED Indicator
NJT5763N	5.85 to 6.725 GHz (Full C-band)	4.90 GHz	950 to 1,825 MHz	10W Linear (+40 dBm min.)	N-type	DC Power +24/+48 VDC (+18 to +60 VDC)	Same as IF Connector	Equipped
NJT5763F					F-type		MS Connector (Separate Port)	
NJT5763NM					N-type			
NJT5763FM					F-type	AC Power Option	IF Connector Supplied by AC PSU	
NJT5763NA					N-type			
NJT5763FA					F-type			

< Specifications >

Item	Specifications
Output Interface	Waveguide, CPR137 (with Groove)
Input Interface	N-type, female (50 ohm) [Model No.: NJT5763N/63NM/63NA] F-type, female (75 ohm) [Model No.: NJT5763F/63FM/63FA]
Output Power @ 1 dB G.C.P.	+39 dBm min. over temperature
Linear Gain	64 dB nom., 58 dB min.
IM3	-24 dBc typ. @total power = +39dBm - 3dB
Requirement for External Reference	[Frequency] 10 MHz (sine-wave)
	[Input Power] -5 to +5 dBm @ Input port
	[Phase Noise] -125 dBc/Hz max. @ 100 Hz
	-135 dBc/Hz max. @ 1 kHz
L.O. Phase Noise	-140 dBc/Hz max. @ 10 kHz
	-60 dBc/Hz max. @ 100 Hz
	-70 dBc/Hz max. @ 1 kHz
	-80 dBc/Hz max. @ 10 kHz
Receive Band Noise Density	-87 dBm/4kHz max. @3.400 to 4.200 GHz
Input V.S.W.R.	2.0 : 1 max.
Output V.S.W.R.	2.0 : 1 max.
Power Requirement / Consumption	+24 / +48 VDC (+18 to +60 VDC) / 75 W typ., 85 W max.
	AC Power Option: 90 to 264 VAC at Indoor AC/DC PSU [Model No.: NJT5763NA/63FA]
Mute	Shut off the HPA in case of L.O. unlocked or no 10 MHz reference signal
LED Indicator	GREEN: L.O. locked / RED: L.O. unlocked or no 10 MHz reference signal
Port for Voltage Input	Same as IF Connector [Model No.: NJT5763N/63F]
	MS Connector (Separate Port) [Model No.: NJT5763NM/63FM]
	IF Connector supplied by AC/DC PSU via IF Cable [Model No.: NJT5763A/63FA]
Temperature Range (ambient)	-40 to +55 °C (operating), -40 to +75 °C (storage)
Waterproof/Dustproof (IP Code)	IP 67
Dimension & Housing (without Interface Connectors)	219.5 mm (L) x 175 mm (W) x 99 mm (H)
	[8.64" (L) x 6.89" (W) x 3.90" (H)]
Weight	3.2 kg [7.0 lbs]

*Note: The contents of this sheet are subject to change without notice.

(1/8)
Rev.07(May 2017) Full C 10W BUC_NJT5763